

Printing date 24.01.2021 Revision: 24.01.2021

#### 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: N-BUTANOL
- CAS Number: 71-36-3
- · EC number:
- 200-751-6
- · Index number: 603-004-00-6
- · Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Petrochem Middle East FZE Dubai
- · Further information obtainable from:



Product safety department. sales@petrocheme.com

### 2 Hazards identification

· Classification of the substance or mixture



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed. Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Acute Tox. 5 H313 May be harmful in contact with skin.

- · Label elements
- · GHS label elements

The substance is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02

2 GHS05

GHS07

· Signal word Danger

(Contd. on page 2)



Printing date 24.01.2021 Revision: 24.01.2021

Trade name: N-BUTANOL

(Contd. of page 1)

· Hazard statements

Flammable liquid and vapour.

Harmful if swallowed.

May be harmful in contact with skin.

Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- · Chemical characterisation: Substances
- · CAS No. Description

71-36-3 butan-1-ol

- · Identification number(s)
- EC number: 200-751-6
- · Index number: 603-004-00-6

#### 4 First aid measures

- Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Call for a doctor immediately.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)



Printing date 24.01.2021 Revision: 24.01.2021

Trade name: N-BUTANOL

(Contd. of page 2)

· For safety reasons unsuitable extinguishing agents: Water with full jet

· Special hazards arising from the substance or mixture No further relevant information available.

· Advice for firefighters

· Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients	with limi	t values tha	t reauire i	monitoring	at the workplace:
Ingremens	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	i ruines iiiu	i i cynii c i	nonnonnig	at the wormplace.

71-36-3 butan-1-ol	
, ,	$300 \text{ mg/m}^3$ , $100 \text{ ppm}$
REL (USA)	Short-term value: C 150 mg/m³, C 50 ppm Skin
	61 mg/m³, 20 ppm
WEL (Great Britain)	Short-term value: 154 mg/m³, 50 ppm Sk

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)



Printing date 24.01.2021 Revision: 24.01.2021

Trade name: N-BUTANOL

(Contd. of page 3)

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve protection:



Tightly sealed goggles

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Colourless
Odour: Alcohol-like
Odour threshold: Not determined.

7

· pH-value (70 g/l) at 20 °C:

· Change in condition

Melting point/freezing point: -89 °C Initial boiling point and boiling range: 116-118 °C

· Flash point: 35 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 340 °C

(Contd. on page 5)



Printing date 24.01.2021 Revision: 24.01.2021

Trade name: N-BUTANOL

	(Contd. of page
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapoumixtures are possible.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	9.4 Vol %
Vapour pressure at 20 °C:	6.7 hPa
Density at 20 °C:	0.81 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water at 20 °C:	77 g/l
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C:	2.95 mPas
Xinematic:	Not determined.
Other information	No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC50	values re	levant for	classification	
-----------	-----------	------------	----------------	--

		• •
Oral	LD50	790 mg/kg (rat)
	LD50	3400 mg/kg (rabbit)
Inhalative	LC50/4 h	8000 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Strong irritant with the danger of severe eye injury.
- · Respiratory or skin sensitisation No sensitising effects known.

ΔF



Printing date 24.01.2021 Revision: 24.01.2021

Trade name: N-BUTANOL

(Contd. of page 5)

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
ADR, IMDG, IATA	1120	
UN proper shipping name		
ADR	1120 BUTANOLS	
IMDG, IATA	BUTANOLS	
Transport hazard class(es)		
ADR, IMDG, IATA		
Class	3 Flammable liquids.	
Citibb	-	
Label	3	
	3	
Packing group	3 III	
Packing group ADR, IMDG, IATA		
Packing group ADR, IMDG, IATA Environmental hazards:		
Label Packing group ADR, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user	III	



Printing date 24.01.2021 Revision: 24.01.2021

Trade name: N-BUTANOL

	(Contd. of p	age 6
· EMS Number:	F-E,S-D	
Transport in bulk according to Annex II	of Marpol	
and the IBC Code	Not applicable.	
Transport/Additional information:		
· ADR		
· Limited quantities (LQ)	LQ7	
Transport category	3	
Tunnel restriction code	D/E	
· UN "Model Regulation":	UN 1120 BUTANOLS, 3, III	

#### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · GHS label elements

The substance is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms







GHS02

GHS05

GHS07

- · Signal word Danger
- · Hazard statements

Flammable liquid and vapour.

Harmful if swallowed.

May be harmful in contact with skin.

Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department.
- · Contact: PME

(Contd. on page 8)



Printing date 24.01.2021 Revision: 24.01.2021

Trade name: N-BUTANOL

(Contd. of page 7)

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - oral – Category 4

Acute Tox. 5: Acute toxicity - dermal - Category 5 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- AE